

Product images	Application	Characteristic	Structure
 	▶ High temperature protective casing ▶ Fire resistant and flame-retardant places	▶ Soft and easy to bend ▶ Arc resistance, voltage resistance, corona resistance ▶ High temperature resistance, water resistance, oil resistance ▶ Ozone resistant, cold resistant, and aging resistant ▶ Thermal insulation	▶ Color: Red / Black Other colors can be customized ▶ Temperature: -40 °C/260 °C
			Can withstand 15-20 minutes at a temperature of 1093 °C
			Can withstand 15-30 seconds at a temperature of 1649 °C
	▶ Inner wall of the pipe: Glass fiber thread woven into the pipe ▶ Pipe coating: Iron oxide red silicone rubber	▶ Electrical insulation ▶ Flame retardant grade VW-1	

Part Number	Internal diameter mm	Wall thickness mm	Tolerance mm	Roll Length m
701-004-20	4	1.5	±0.15	20
701-006-20	6	1.5	±0.15	20
701-008-20	8	1.5	±0.15	20
701-010-20	10	2	±0.20	20
701-011-20	11	2	±0.20	20
701-013-20	13	2	±0.20	20
701-016-20	16	2	±0.20	20
701-019-20	19	2	±0.20	20
701-022-20	22	2	±0.20	20
701-025-20	25	2	±0.30	20
701-029-20	29	2	±0.30	20
701-032-20	32	2	±0.30	20
701-035-20	35	3	±0.30	20
701-038-20	38	3	±0.30	20
701-041-20	41	3	±0.30	20
701-045-20	45	3	±0.30	20
701-048-20	48	3	±0.30	20
701-051-20	51	3	±0.35	20
701-057-20	57	3.5	±0.35	20
701-060-20	60	3.5	±0.35	20
701-064-20	64	3.5	±0.35	20
701-067-20	67	3.5	±0.35	20
701-070-20	70	3.5	±0.40	20
701-073-20	73	3.5	±0.40	20
701-076-20	76	4	±0.40	20
701-083-20	83	4	±0.40	20
701-089-20	89	4	±0.50	20
701-095-20	95	4	±0.50	20
701-102-20	102	5	±0.50	20
701-114-20	114	5	±0.50	20
701-121-20	121	5	±0.50	20
701-127-20	127	5	±0.60	20

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.